FARMTRAC FT25G

ARMITRA

A viable alternative to a diesel compact tractor

New all-electric FT25G tractor from Farmtrac. All the functions and features of a compact tractor, with the benefits of electric power. A compact machine designed for a number of applications including greenhouse work, municipalities, equestrian centres and more, for when you need quieter, cleaner machinery.

ax4

reesinkagriculture.co.uk

An agricultural machinery partner with great service and great value. Great Choice. Great Performance. Great Value. Great Results





FARMTRAC FT25G

Motor	
Туре	Three phase AC induction motor
Power (kW)	18
Battery Pack	
Туре	NMC
Pack capacity	300AH
Charge time	8hrs from 0-100%
Transmission	
Туре	3-range constant mesh
Differential lock	Standard
Brakes	
Туре	Oil immersed brakes
Parking brake	Independent
Three Point Linkage	
Category	Cat 1N
Hydraulics	
Rear linkage control	Position control
Lift capacity (kg)	450 (at hitch point)
Pump capacity (lpm)	15.9
Auxiliary valve	1DA (2 nos.)
РТО	
Rear PTO (rpm)	540
Mid PTO (rpm)	2200 (not available on Ag tyres)
Steering	
Туре	Hydrostatic power steering
Front Axle	
Туре	Selectable 4WD
Dimensions	
Length (mm)	2754
Width (mm)	1470
Height (mm)	2207
Wheelbase (mm)	1551
Weight (kg)	1208



22kW battery pack







Zero emissions & low noise

Standard Equipment

- 72V lithium-ion battery technology
- Zero emissions
- Minimal noise and vibration
- Onboard battery charger
- Easy to view instrument panel
- Three range transmission
- Selectable 4WD
- Independent 540 rpm rear PTO
- Rear hydraulic spool valves
- Rear work lamp Road lighting kit
- Flashing beacon (ROPS mounted)
- Front weight bracket
- Independent parking brake
- Rear mounted tool box

Optional Equipment

- Agricultural tyres
- Turf tyres
 Industrial tyres
- 2500 front loader

An agricultural machinery partner with great service and great value. Great Choice. Great Performance. Great Value. Great Results



Reesink UK LTD is authorised and regulated by the Financial Conduct Authority. Images shown for illustration only.

Specifications correct at time of publishing but are subject to change at any time.

